

NEK2125U



**ENGINEERING CODE**  
861CA51



**REFRIGERANT**  
R-290



**POWER SUPPLY**  
220-240 V 50 Hz



**APPLICATION**  
LBP



**MOTOR TYPE**  
CSIR



**STANDARD**  
EN12900



**COOLING CAPACITY**  
198 W



**EFFICIENCY**  
1.1 W/W



DATA

GENERAL DATA

Model	NEK2125U
Type	Hermetic Reciprocating
Technology	ON/OFF
Compressor Application	LBP
Expansion Device	Capillary Tube or Expansion Valve
Compressor Cooling	Fan/220
HP	1/3
Starting Torque	HST
Plant	SLOVAKIA

ELECTRICAL DATA

Start Winding Resistance	28.9 Ω at 25°C
Run Winding Resistance	6.8 Ω at 25°C

## MECHANICAL DATA

Displacement	7.28 cm <sup>3</sup>
Oil Charge	350 ml
Oil Type	AB
Oil Viscosity	ISO32
Weight	10.4 Kg

## ELECTRICAL COMPONENTS

Start Capacitor	53-64 µf/330 V
CSR CSIR BOX	No
Starting Device Type	RELAY
Starting Device Description	MTRP-0029*
Overload Protection	T0525/G6

## EXTERNAL CHARACTERISTICS

Base Plate	SMALL
Tray Holder	NO

Connector	Internal Diameter	Shape	Material
Suction	8.1 mm	SLANTED 42°	COPPER
Discharge	6.1 mm	STRAIGHT	COPPER
Process	6.1 mm	SLANTED 42°	COPPER

## PERFORMANCE

### TESTED CONDITIONS

Tested Refrigerant	R-290
Tested Application	LBP
Tested Standard	EN12900
Tested Cooling	Fan
Tested Voltage	220 V
Tested Frequency	50 Hz
Refrigerant Temperature	Dew

**RATED POINTS**

Condensing Temperature °C	Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
40	-35	198	1.1	180	-	2.27

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

**PERFORMANCE CURVE****Condensing Temperature 35°C**

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-40	175	1.11	157	-	1.91
-35	214	1.21	176	-	2.35
-30	263	1.34	196	-	2.89
-25	324	1.51	215	-	3.58
-20	401	1.74	231	-	4.45
-15	497	2.03	244	-	5.53
-10	613	2.43	253	-	6.86

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

**PERFORMANCE CURVE****Condensing Temperature 45°C**

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-40	147	0.91	161	-	1.77
-35	181	1.00	181	-	2.18
-30	224	1.10	203	-	2.70
-25	277	1.23	226	-	3.36
-20	345	1.39	248	-	4.19
-15	428	1.60	268	-	5.24
-10	532	1.87	285	-	6.54

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

**PERFORMANCE CURVE****Condensing Temperature 55°C**

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-30	184	0.90	205	-	2.47
-25	229	0.99	230	-	3.09
-20	286	1.12	257	-	3.89
-15	359	1.27	282	-	4.90
-10	449	1.47	306	-	6.17

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

## ENVELOPE



## EXTERNAL DIMENSIONS

