

# MODELS AND PERFORMANCE MEDIUM TEMPERATURE (MBP)

## MEDIUM TEMPERATURE

R449A

R452A

CONDENSING UNITS MODELS	Compressors		Cooling capacity (kW) RGT20° @+32°C			Max Power input (kW)	Dimensions (mm)**			Weight	MCC	Fan		Liquid receiver	Connection diameters	
	Displ. (cc)	HP	-10°C	-10°C	+10°C		W	D	H	Net (kg)	(A)	Number of fans	Airflow (m³/h)	dm³	Suction (")	Liquid (")
<b>Compressor 230V-1ph-50Hz - Fan 230V-1ph-50Hz</b>																
UEMT6144GK	4	1/4-	-	0,38	0,21		302	480	226	16,6	1,68	1	300	0,6	3/8"	1/4"
UEMT6152GK	4,5	1/4	-	0,4	0,24		302	480	226	16,6	1,94	1	300	0,6	3/8"	1/4"
UEMT6165GK	5,5	1/3	0,45	0,49	0,29		302	480	254	17,3	2,32	1	420	1,1	3/8"	1/4"
UNEU6210GK	7,3	1/3	0,61	0,69	0,4		340	475	296	21	3,11	1	595	1,1	3/8"	1/4"
UNEU6212GK	8,8	1/2	0,73	0,82	0,49		340	465	296	20,1	4,25	1	595	1,1	3/8"	1/4"
UNEU6215GK	12,1	1/2	1	1,13	0,67		395	480	324	29	5,23	1	640	1,1	3/8"	1/4"
UNEU6220GK	14,3	3/4	1,18	1,32	0,76		398	471	323	25,3	5,55	1	640	2,3	1/2"	3/8"
UNT6220GK	14,5	3/4	1,47	1,24	0,71		395	500	324	32,3	5,15	1	640	2,3	1/2"	3/8"
UNT6222GK	17,4	3/4	1,32	1,43	0,85		395	500	324	32,5	7,73	1	640	2,3	1/2"	3/8"
UNT6224GK	20,4	1	UD	UD	UD		UD	UD	UD	UD	UD	UD	UD	UD	UD	UD
UNT6226GK	22,4	1+	1,71	1,85	1,04		405	485	372	33,6	7,27	1	700	2,3	1/2"	3/8"
UNJ9232GK	26,1	1,25	1,9	2,05	1,25		440	600	372	41,5	8,12	1	1450	3,9	5/8"	3/8"
UNJ9238GK	32,7	1,5	2,29	2,47	1,58		440	600	372	43	10,1	1	1300	3,9	5/8"	3/8"
<b>Compressor 400V-3ph-50Hz - Fan 230V-1ph-50Hz or 400V-3ph-50Hz</b>																
UNJ9232GS	26,1	1,25	1,95	2,1	1,17		440	600	372	39,7	3,35	1	1450	3,9	5/8"	3/8"
UNJ9238GS	32,7	1,5	2,26	2,55	1,61		440	600	372	42	4,49	1	1300	3,9	5/8"	3/8"
UNJX6250GS	38	2	3,11	3,35	1,99		612	657	494	45	3,4	1	3200	3,9	1/2"	3/8"
USE6015GS	-	2	3,6	3,61	2,1		612	657	494	56	4,4	1	3200	3,9	7/8"	3/8"
USE6018GS	-	2,5	4,2	4,2	2,4		612	657	494	57	5,9	1	3200	3,9	7/8"	3/8"
USE6021GS	-	3	4,69	4,68	2,68		612	657	494	57	6,1	1	3200	3,9	7/8"	3/8"