

# MODELS AND PERFORMANCE LOW TEMPERATURE (LBP)

## LOW TEMPERATURE

R449A

R452A

CONDENSING UNITS MODELS	Compressors		Cooling capacity (Kw) RGT20* @+32°C		Max Power input (Kw)	Dimensions (mm)**			Weight	MCC	Fan		Liquid receiver	Connection diameters	
	Displ. (cc)	HP	-35°C	-35°C	+10°C	W	D	H	Net (kg)	(A)	Number of fans	Airflow (m³/h)	dm³	Suction (")	Liquid (")

### Compressor 230V-1ph-50Hz - Fan 230V-1ph-50Hz

UEMT2117GK	4,5	1/4	-	0,14	0,1	290	430	226	17,1	1,4	1	300	0,5	3/8"	1/4"
UEMT2121GK	5,2	1/3	-	0,18	0,17	290	430	226	20	1,46	1	300	0,5	3/8"	1/4"
UEMT2125GK	6,0	1/3+	-	0,20	0,20	435	308	254	15,4	1,2	1	420	1,1	3/8"	1/4"
UEMT2130GK	6,8	1/2-	-	0,22	0,23	300	435	254	15,4	2,5	1	420	1,1	3/8"	1/4"
UNEU2140GK	8,8	1/2	-	0,25	0,75	340	475	296	20,9	3,05	1	595	1,1	3/8"	1/4"
UNEU2155GK	12,1	3/4	-	0,32	0,37	340	475	296	22,2	4,21	1	595	1,1	3/8"	1/4"
UNEU2168GK	14,3	3/4	-	0,10	0,42	340	502	296	23	4,8	1	460	1,1	3/8"	1/4"
UNT2178GK	17,4	1-	-	0,44	0,46	340	494	296	27,7	4,24	1	460	1,2	3/8"	1/4"
UNT2180GK	20,4	1	-	0,55	0,55	340	494	296	28,6	5,8	1	460	1,2	3/8"	1/4"
UNT2192GK	22,4	1+	-	0,59	0,59	395	500	324	32,8	5,5	1	800	2,3	3/8"	3/8"
UNT2210GK	26,2	1,25	-	0,69	0,71	395	494	324	34,6	7,18	1	800	2,3	1/2"	3/8"
UNT2212GK	27,8	1,5	-	0,40	0,73	395	500	324	36	5,25	1	800	2,3	1/2"	3/8"
UNJ2192GK	26,1	1,25	-	0,65	0,70	404	505	324	35,3	4,75	1	800	2,3	1/2"	3/8"
UNJ2212GK	34,4	1,5	-	0,83	0,81	404	505	324	37,9	6,5	1	800	2,3	5/8"	3/8"

### Compressor 400V-3ph-50Hz - Fan 230V-1ph-50Hz or 400V-3ph-50Hz

UNJ2212GS	34,4	1,5	-	0,85	0,72	405	505	324	36,5	2,38	1	800	2,3	5/8"	3/8"
UNJX2219GS	38	2	-	1,15	1,21	612	657	494	45	-	1	3200	3,9	1/2"	3/8"
USE2006GS	-	2	1,2	1,28	1,34	612	657	494	57	3,5	1	3200	3,9	7/8"	3/8"
USE2008GS	-	2,5	1,51	1,62	1,66	612	657	494	57	3,9	1	3200	3,9	7/8"	3/8"