



Refrigerant	R449A Dew Point
<b>High Side Properties:</b>	
Condensing Temperature, °C	45.00
Abs. Condensing Pressure, bar	18.86
Dew Point, °C	45.00
Bubble Point, °C	40.70
Saturated vapour enthalpy, kJ/kg	414.00
Specific volume of saturated vapour, dm <sup>3</sup> /kg	11.30
<b>Low Side Properties:</b>	
Evaporating Temperature, °C	-10.00
Evaporating Abs. Pressure, bar	3.61
Dew Point, °C	-10.00
Bubble Point, °C	-15.40
With vapour at, °C	20.00
Specific volume, dm <sup>3</sup> /kg	72.50
Enthalpy, kJ/kg	421.00
<b>Operating Conditions:</b>	
Evaporating Temperature, °C	-10.00
Condensing Temperature, °C	45.00
Suction Return Temperature, °C	20.00
Subcooling, K	0.00
Compressor Selected	ZB21KCE-TFD

**PERFORMANCE AT SPECIFIED OPERATING POINT  
ZB21KCE-TFD Data at 50 Hz**

Cooling Capacity, kW	4.87
Power, kW	2.34
COP	2.08
Current at 400 V, A	4.46
Suction Mass Flow, g/s	30.70
Heating Capacity, kW	7.10

**COMPRESSOR MECHANICAL AND PHYSICAL DATA**

Displacement @ 50 Hz, m <sup>3</sup> /h	8.61
Length/Width, mm	243/244
Height, mm	391
Net Weight, kg	27.3
Rotalock Suction, inch	1 1/4
Rotalock Discharge, inch	1
Oil Quantity, l	1.24
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	190 x 190 (8.5)
Sound Pressure @ 1m (MT), dBA	58
Sound Power (MT), dBA	69
Sound Conditions (MT, Temperatures: Evap./Cond./Suction at freq./speed)	-10 / 45 / 20 °C at 50 Hz
PED Category	1
Max. Internal Free Volume, l	2.50
High Side PS gauge, bar	32
Low Side PS gauge, bar	21
Low Side TS Max., °C	50
Low Side TS Min., °C	-35
Refrigerant's GWP	1397
Refrigerant's classification	A1

**COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)**

Maximum Operating Current, A	7.2
Locked Rotor Current, A	40
Winding Resistance, ohm	4.83
Default Enclosure Class	IP 21 (IEC 34)

**ACCESSORIES INCLUDED**

Discharge Temperature Protection	Internal Thermodisk
Mounting Grommets	Standard

***ACCESSORIES OPTIONAL***

Crankcase Heater  
Oil Control System  
Sound Attenuation  
Rotalock valves

70 W External  
ALCO Trax-Oil OM3  
Sound Shell (10dBA)  
suction and discharge

MODEL NUMBER	A±3.0	B	C	D±3.0	F	G_	H
ZF06K4/K4E	368.7	343.1	243.8	202.2	279.4	68.9	43.4
ZF08K4/K4E ZF09K4/K4E	391.3	365.7	263.7	222.1	302.0	74.6	49.1
ZF11K4/K4E	405.0	379.4	276.4	234.8	315.7	74.6	49.1
ZS15K4/K4E	368.7	343.1	243.8	202.2	OMIT	68.9	43.4
ZS19K4/K4E ZS21K4/K4E	391.3	365.7	263.7	222.1	OMIT	74.6	49.1
ZS26K4/K4E	405.0	379.4	276.4	234.8	OMIT	74.6	49.1
ZB15KC/KCE ZB19KC/KCE	368.7	343.1	243.8	202.2	OMIT	68.9	43.4
ZB21KC/KCE	391.3	365.7	263.7	222.1	OMIT	74.6	49.1
ZB26KC/KCE	405.0	379.4	276.4	234.8	OMIT	74.6	49.1
ZB29KCE	423.4	397.1	293.5	252.0	OMIT	74.6	49.1

