



Refrigerant	R449A Dew Point
High Side Properties:	
Condensing Temperature, °C	45.00
Abs. Condensing Pressure, bar	18.86
Dew Point, °C	45.00
Bubble Point, °C	40.70
Saturated vapour enthalpy, kJ/kg	414.00
Specific volume of saturated vapour, dm ³ /kg	11.30
Low Side Properties:	
Evaporating Temperature, °C	-35.00
Evaporating Abs. Pressure, bar	1.29
Dew Point, °C	-35.00
Bubble Point, °C	-40.70
With vapour at, °C	20.00
Specific volume, dm ³ /kg	213.00
Enthalpy, kJ/kg	425.00
Operating Conditions:	
Evaporating Temperature, °C	-35.00
Condensing Temperature, °C	45.00
Suction Return Temperature, °C	20.00
Subcooling, K	0.00
Compressor Selected	ZF25K5E-TFD

PERFORMANCE AT SPECIFIED OPERATING POINT
ZF25K5E-TFD Data at 50 Hz

Cooling Capacity, kW	4.36
Power, kW	4.23
COP	1.03
Current at 400 V, A	7.96
Suction Mass Flow, g/s	26.70
Heating Capacity, kW	8.38

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Displacement @ 50 Hz, m ³ /h	21.4
Length/Width, mm	246/257
Height, mm	452
Net Weight, kg	39.5
Rotalock Suction, inch	1 1/4
Rotalock Discharge, inch	1 1/4
Stub Suction, inch	7/8
Stub Discharge, inch	3/4
Oil Quantity, l	1.89
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	190 x 190 (0)
Sound Pressure @ 1m (LT), dBA	70
Sound Power (LT), dBA	81
Sound Conditions (LT, Temperatures: Evap./Cond./Suction at freq./speed)	-35 / 40 / 20 °C at 50 Hz
PED Category	1
Max. Internal Free Volume, l	5.70
High Side PS gauge, bar	28.8
Low Side PS gauge, bar	21
Refrigerant's GWP	1397
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	16
Locked Rotor Current, A	102
Winding Resistance, ohm	1.72
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Discharge Temperature Protection	Discharge line thermostat
Mounting Grommets	Standard

ACCESSORIES OPTIONAL

Crankcase Heater
Liquid Injection
Oil Control System
Rotalock valves

70 W External
DTC Valve
ALCO Trax-Oil OM3
suction and discharge

ZF25K5E

VAPOR INJECTION FITTING
(ROTALOCK)
1.00-14 UNS-2A

31.75
ROTALOCK
DISCHARGE

31.75
ROTALOCK
SUCTION

