

Refrigerant	R410A Dew Point
High Side Properties:	
Condensing Temperature, °C	45.00
Abs. Condensing Pressure, bar	27.18
Dew Point, °C	45.00
Bubble Point, °C	44.90
Saturated vapour enthalpy, kJ/kg	424.00
Specific volume of saturated vapour, dm ³ /kg	8.40
Low Side Properties:	
Evaporating Temperature, °C	0.00
Evaporating Abs. Pressure, bar	7.97
Dew Point, °C	0.00
Bubble Point, °C	-0.10
With vapour at, °C	10.00
Specific volume, dm ³ /kg	35.00
Enthalpy, kJ/kg	431.00
Operating Conditions:	
Evaporating Temperature, °C	0.00
Condensing Temperature, °C	45.00
Suction Superheat, K	10.00
Subcooling, K	0.00
Compressor Selected	ZP72KCE-TFD

**PERFORMANCE AT SPECIFIED OPERATING POINT
ZP72KCE-TFD Data at 50 Hz**

Cooling Capacity, kW	13.75
Power, kW	4.53
COP	3.04
Current at 400 V, A	8.14
Suction Mass Flow, g/s	88.00
Heating Capacity, kW	18.05

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Displacement @ 50 Hz, m ³ /h	11.7
Length/Width, mm	246/246
Height, mm	455
Net Weight, kg	39.9
Stub Suction, inch	7/8
Stub Discharge, inch	1/2
Oil Quantity, l	1.66
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF
Base mounting (hole dia), mm	190 x 190 (19)
Sound Pressure @ 1m (HT), dBA	59
Sound Power (HT), dBA	70
Sound Power with Sound Shell (HT), dBA	63
Sound Conditions (HT, Temperatures: Evap./Cond./Suction at freq./speed)	7 / 54 / 18 °C at 50 Hz
PED Category	1
Max. Internal Free Volume, l	3.90
High Side PS gauge, bar	45
Low Side PS gauge, bar	29.5
Low Side TS Min., °C	-35
Refrigerant's GWP	2088
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	15
Locked Rotor Current, A	75
Winding Resistance, ohm	2.26
Default Enclosure Class	IP 21 (IEC 34)

ACCESSORIES INCLUDED

Mounting Grommets	Rubber Grommet For Single
-------------------	---------------------------

ACCESSORIES OPTIONAL

Enclosure Class	IP 54
-----------------	-------

ZP61KCE, ZP72KCE, ZP83KCE

