



Refrigerant	R410A Dew Point
<b>High Side Properties:</b>	
Condensing Temperature, °C	45.00
Abs. Condensing Pressure, bar	27.18
Dew Point, °C	45.00
Bubble Point, °C	44.90
Saturated vapour enthalpy, kJ/kg	424.00
Specific volume of saturated vapour, dm <sup>3</sup> /kg	8.40
<b>Low Side Properties:</b>	
Evaporating Temperature, °C	0.00
Evaporating Abs. Pressure, bar	7.97
Dew Point, °C	0.00
Bubble Point, °C	-0.10
With vapour at, °C	10.00
Specific volume, dm <sup>3</sup> /kg	35.00
Enthalpy, kJ/kg	431.00
<b>Operating Conditions:</b>	
Evaporating Temperature, °C	0.00
Condensing Temperature, °C	45.00
Suction Superheat, K	10.00
Subcooling, K	0.00
Compressor Selected	ZP122KCE-TFD

**PERFORMANCE AT SPECIFIED OPERATING POINT  
ZP122KCE-TFD Data at 50 Hz**

Cooling Capacity, kW	23.90
Power, kW	7.43
COP	3.21
Current at 400 V, A	14.98
Suction Mass Flow, g/s	152.50
Heating Capacity, kW	30.90

**COMPRESSOR MECHANICAL AND PHYSICAL DATA**

Displacement @ 50 Hz, m <sup>3</sup> /h	19.5
Length/Width, mm	297/262
Height, mm	559
Net Weight, kg	48.8
Stub Suction, inch	1 1/8
Stub Discharge, inch	7/8
Oil Quantity, l	2.51
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF
Base mounting (hole dia), mm	190 x 190 (19)
Sound Pressure @ 1m (HT), dBA	61
Sound Power (HT), dBA	72
Sound Conditions (HT, Temperatures: Evap./Cond./Suction at freq./speed)	7 / 54 / 18 °C at 50 Hz
PED Category	2
Max. Internal Free Volume, l	7.20
High Side PS gauge, bar	45
Low Side PS gauge, bar	29.5
Low Side TS Max., °C	50
Low Side TS Min., °C	-35
Refrigerant's GWP	2088
Refrigerant's classification	A1

**COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)**

Maximum Operating Current, A	21.6
Locked Rotor Current, A	139
Winding Resistance, ohm	1.17
Default Enclosure Class	IP 21 (IEC 34)

**ACCESSORIES INCLUDED**

Discharge Temperature Protection	ASTP Therm-O-Disc In Scroll
----------------------------------	-----------------------------

**ACCESSORIES OPTIONAL**

ZP104KCE  
ZP122KCE  
ZP143KCE

