



Minimum Evaporating Temp. With:

- 10 K Suction Superheat
- Maximum Evaporating Temperature

Suction Superheat 10.0K

Liquid Subcooling 0.0K

Evaporating Temperature, °C

Cond °C	Cooling Capacity, kW									
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0
25.0	42.40	52.50	64.30	78.00	93.90	112.00	120.00	132.50		
30.0	39.90	49.60	61.00	74.10	89.30	106.50	114.50	126.50	137.50	149.00
35.0	37.40	46.70	57.50	70.00	84.50	101.00	108.50	120.00	130.00	141.00
40.0	34.90	43.70	53.90	65.80	79.40	95.10	102.00	113.00	123.00	133.00
45.0		40.60	50.20	61.30	74.10	88.90	95.30	105.50	115.00	125.00
50.0			46.30	56.60	68.60	82.30	88.40	98.10	107.00	116.00
55.0				51.70	62.70	75.40	81.00	90.00	98.10	106.50
60.0					56.50	68.00	73.10	81.40	88.80	96.70
65.0					49.60	59.90	64.50	71.80	78.40	85.60

50 Hz

ZP385KCE-TWD

R410A Dew Point

Cond °C	Power, kW									
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0
25.0	14.45	14.65	14.95	15.25	15.60	16.00	16.15	16.40		
30.0	16.20	16.35	16.50	16.75	17.05	17.40	17.55	17.80	18.00	18.20
35.0	18.20	18.20	18.30	18.50	18.75	19.05	19.20	19.40	19.60	19.80
40.0	20.40	20.30	20.30	20.40	20.60	20.90	21.00	21.30	21.50	21.70
45.0		22.70	22.70	22.70	22.80	23.10	23.20	23.40	23.60	23.80
50.0			25.30	25.30	25.40	25.60	25.70	25.90	26.10	26.30
55.0				28.30	28.30	28.40	28.50	28.70	28.90	29.10
60.0					31.60	31.70	31.80	32.00	32.10	32.30
65.0					35.40	35.50	35.50	35.70	35.80	36.00

Cond °C	Current at 400 V, A									
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0
25.0	29.50	29.77	30.07	30.41	30.80	31.26	31.45	31.77		
30.0	31.61	31.77	31.98	32.26	32.61	33.03	33.23	33.55	33.84	34.16
35.0	34.06	34.10	34.22	34.42	34.72	35.11	35.30	35.61	35.91	36.23
40.0	36.91	36.83	36.85	36.97	37.21	37.57	37.75	38.06	38.35	38.68
45.0		40.04	39.96	40.00	40.17	40.49	40.66	40.95	41.24	41.58
50.0			43.62	43.57	43.68	43.95	44.10	44.38	44.67	45.00
55.0				47.78	47.81	48.02	48.16	48.43	48.71	49.03
60.0					52.65	52.80	52.92	53.17	53.44	53.76
65.0					58.28	58.37	58.47	58.69	58.94	59.25

Cond °C	Suction Mass Flow, g/s									
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0
25.0	231.00	283.00	342.00	411.00	489.00	578.00	617.00	678.00		
30.0	228.00	280.00	340.00	408.00	487.00	575.00	614.00	676.00	731.00	789.00
35.0	225.00	277.00	337.00	405.00	483.00	572.00	611.00	672.00	727.00	785.00
40.0	222.00	274.00	333.00	401.00	479.00	567.00	606.00	667.00	722.00	780.00
45.0		270.00	329.00	397.00	474.00	562.00	600.00	661.00	716.00	773.00
50.0			325.00	392.00	468.00	555.00	593.00	654.00	708.00	766.00
55.0				386.00	461.00	548.00	585.00	646.00	700.00	757.00
60.0					455.00	540.00	577.00	637.00	691.00	748.00
65.0					448.00	532.00	569.00	629.00	682.00	739.00

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Displacement @ 50 Hz, m ³ /h	60.8
Length/Width, mm	447/427
Height, mm	724
Net Weight, kg	176
Stub Suction, inch	1 5/8
Stub Discharge, inch	1 3/8
Oil Quantity, l	6.3
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF
Base mounting (hole dia), mm	266.7 x 266.7 (22.6)
Sound Pressure @ 1m (HT), dBA	74
Sound Power (HT), dBA	85
Sound Conditions (HT, Temperatures:	7 / 54 / 18 °C at 50 Hz
Evap./Cond./Suction at freq./speed)	
PED Category	2
Max. Low Side Internal Free Volume, l	28.7
Max. Internal Free Volume, l	31.6
High Side PS gauge, bar	45
Low Side PS gauge, bar	29.5
Low Side TS Max., °C	50
Low Side TS Min., °C	-35
Refrigerant's GWP	2088
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	65.4
Locked Rotor Current, A	310
Winding Resistance, ohm	0.36
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Discharge Temperature Protection	Internal Thermistor
Discharge Temperature Protection	PTC in Scroll Discharge Port
Enclosure Class	IP 54
Mounting Grommets	Standard
Mounting Grommets	Rubber Grommet For Single
Oil Charge	
Oil Service Valve	Schraeder Valve
Check Valve	Discharge Low Leak Check Valve

ACCESSORIES OPTIONAL

Crankcase Heater		102 W External
Mounting Grommets		Rubber Grommet For Parallel
Adapter Kit		Operation
Oil Control System		R1"3/4 - B1"3/8 For TPTL for
	ALCO Trax-Oil OM4	Parallel Operation

MOTOR OPTIONS

Motor Code	Power Supply	Nominal Voltage, V	Start Connection	DOL Connection	Amps Factor
TWD	380-420 V / 3~ / 50 Hz	400		Y	1.00
TWD	460 V / 3~ / 60 Hz	460		Y	1.04