

Refrigerant	R410A Dew Point
<b>High Side Properties:</b>	
Condensing Temperature, °C	45.00
Abs. Condensing Pressure, bar	27.18
Dew Point, °C	45.00
Bubble Point, °C	44.90
Saturated vapour enthalpy, kJ/kg	424.00
Specific volume of saturated vapour, dm <sup>3</sup> /kg	8.40
<b>Low Side Properties:</b>	
Evaporating Temperature, °C	0.00
Evaporating Abs. Pressure, bar	7.97
Dew Point, °C	0.00
Bubble Point, °C	-0.10
With vapour at, °C	10.00
Specific volume, dm <sup>3</sup> /kg	35.00
Enthalpy, kJ/kg	431.00
<b>Operating Conditions:</b>	
Evaporating Temperature, °C	0.00
Condensing Temperature, °C	45.00
Suction Superheat, K	10.00
Subcooling, K	0.00
Compressor Selected	ZPD154KCE-TFD

**PERFORMANCE AT SPECIFIED OPERATING POINT  
ZPD154KCE-TFD Data at 50 Hz**

Cooling Capacity, kW	30.00
Power, kW	9.25
COP	3.24
Current at 400 V, A	16.93
Suction Mass Flow, g/s	192.00
Heating Capacity, kW	38.80

**COMPRESSOR MECHANICAL AND PHYSICAL DATA**

Displacement @ 50 Hz, m <sup>3</sup> /h	24.9
Length/Width, mm	314/285
Height, mm	552
Net Weight, kg	65.3
Rotalock Suction, inch	1 3/4
Rotalock Discharge, inch	1 1/4
Stub Suction, inch	1 3/8
Stub Discharge, inch	7/8
Oil Quantity, l	3.25
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF
Base mounting (hole dia), mm	190 x 190 (0)
Sound Pressure @ 1m (HT), dBA	66
Sound Power (HT), dBA	77
Sound Conditions (HT, Temperatures: Evap./Cond./Suction at freq./speed)	7 / 54 / 18 °C at 50 Hz
PED Category	2
Max. Internal Free Volume, l	14.0
High Side PS gauge, bar	45
Low Side PS gauge, bar	29.5
Low Side TS Max., °C	50
Low Side TS Min., °C	-35
Refrigerant's GWP	2088
Refrigerant's classification	A1

**COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)**

Maximum Operating Current, A	31
Locked Rotor Current, A	140
Winding Resistance, ohm	1.11
Default Enclosure Class	IP 21 (IEC 34)

**ACCESSORIES INCLUDED**

Enclosure Class	IP21
Motor Protection Device	INT69SCY2
Mounting Grommets	Hard Mounts for Paralleling
Oil Charge	
Oil Service Valve	Schraeder Valve
Digital Control	Integrated Solenoid Valve
Check Valve	Discharge Low Leak Check Valve

***ACCESSORIES OPTIONAL***

Crankcase Heater	66 W External
Discharge Temp Protection	
Mounting Grommets	Rubber Grommet For Single
Digital Control	Digital Valve Coil 24V
Digital Control	Digital Valve Coil 230V
Adapter Kit	R1"1/4 -B 1"1/8 For TPTL for Parallel Operation

# ZP154,182KCE - TFD

