

**032F5053****Elektromagnetski ventil, EVU 2, Lemni priključak, ODF, Funkcija: NC**

Proizvod je povučen.

Funkcija: NC, Veličina ulaza [mm]: 6, Vrsta ulaznog priključka: Lemni priključak, ODF, Veličina izlaza [mm]: 6, Vrsta izlaznog priključka: Lemni priključak, ODF, Opcija ručnog rukovanja: Ne

**PRODUCT DETAILS**

<b>Bruto težina</b>	0.115 Kilogram
<b>Neto težina</b>	0.078 Kilogram
<b>Volumen</b>	0.281 Liter
<b>EAN</b>	5702428049986
<b>Type</b>	EVU 2
<b>Product group</b>	Magnetski ventili
<b>Product Name Description</b>	Elektromagnetski ventil
<b>China RoHS compliance</b>	Yes with exemptions
<b>Contains batteries</b>	No
<b>Cv vrijednost [gal/min]</b>	0.23 gal/min
<b>EU RoHS compliance</b>	Yes with exemptions
<b>EU RoHS exemption clause</b>	6(a) 6(c)
<b>Funkcija</b>	NC
<b>Funkcionalno</b>	Ne
<b>Količina po obliku pakiranja</b>	40 pc
<b>Kv vrijednost [m<sup>3</sup>/h]</b>	0.2 m <sup>3</sup> /h
<b>Maks. radni tlak [bar]</b>	70 bar
<b>Maks. radni tlak [psig]</b>	1015 psig
<b>MinODP [bar]</b>	0.02 bar
<b>MOP (maksimalni radni tlak) [bar/psi]</b>	Coil Dependent
<b>Napomena o rasponu temperature medija</b>	Defrost max. 130°C/265°F
<b>Oblik ambalaže</b>	Industrijsko pakiranje
<b>Odobrenje</b>	EAC LLC CDC TYSK UR
<b>Opcija ručnog rukovanja</b>	Ne
<b>Oznaka vrste</b>	Elektromagnetski ventil, lem
<b>Pribor proizvoda</b>	Pribor za elektromagnetski ventil
<b>Radne tvari</b>	R1233zd(E) R1234yf R1234ze(E) R1270 R134a R22/R407C R23 R290



## PRODUCT DETAILS

---

	R32
	R404A/R507A
	R407A
	R407F
	R407H
	R410A
	R422B
	R422D
	R438A
	R444B
	R448A
	R449A
	R449B
	R450A
	R452A
	R452B
	R454A
	R454B
	R454C
	R455A
	R463A
	R513A
	R513B
	R515A
	R515B
	R516A
	R600
	R600a
	R744
<b>Radne tvari koje je odobrio UL</b>	R1233zd(E)
	R134a
	R22
	R23
	R290
	R404A
	R407A
	R407C
	R407F
	R407H
	R410A
	R422B
	R422D
	R438A
	R448A
	R449A
	R449B
	R450A
	R452A
	R463A
	R507A
	R513A
	R513B
	R515A
	R515B
	R516A

---

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## PRODUCT DETAILS

	R744
Raspon temperature medija [°C] [Max.]	105 °C
Raspon temperature medija [°C] [Min.]	-40 °C
Raspon temperature medija [°F] [maks.]	221 °F
Raspon temperature medija [°F] [min.]	-40 °F
SCIP dossier no.	850a5e3e-abe8-4821- a4ed-92e9c0410196
Smjer	Ravno
Sustav pogona [mm]	9 mm
Svitak	Ne
Temperatura okoliša	-40 - Coil dependent
Tvari s popisa kandidata u skladu s Uredbom REACH	Lead (CAS no. 7439-92-1)
Veličina izlaza [mm]	6 mm
Veličina ulaza [mm]	6 mm
Vrsta izlaznog priključka	Lemni priključak, ODF
Vrsta ulaznog priključka	Lemni priključak, ODF

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)