

**032F5027****Elektromagnetski ventil, EVU 3, Lemni priključak, ODF, Funkcija: NC**

Funkcija: NC, Veličina ulaza [mm]: 10, Vrsta ulaznog priključka: Lemni priključak, ODF, Veličina izlaza [mm]: 10, Vrsta izlaznog priključka: Lemni priključak, ODF, Opcija ručnog rukovanja: Ne

**PRODUCT DETAILS**

<b>Bruto težina</b>	0.101 Kilogram
<b>Neto težina</b>	0.06 Kilogram
<b>Volumen</b>	0.281 Liter
<b>EAN</b>	5702428024693
<b>Type</b>	EVU 3
<b>Product group</b>	Magnetski ventili
<b>Product Name Description</b>	Elektromagnetski ventil
<b>China RoHS compliance</b>	Yes with exemptions
<b>Contains batteries</b>	No
<b>Cv vrijednost [gal/min]</b>	0.4 gal/min
<b>EU RoHS compliance</b>	Yes with exemptions
<b>EU RoHS exemption clause</b>	6(a) 6(c)
<b>Funkcija</b>	NC
<b>Funkcionalno</b>	Ne
<b>Količina po obliku pakiranja</b>	40 pc
<b>Kompatibilnost lubrikanata</b>	AB MO PAG PAO POE PVE
<b>Kv vrijednost [m<sup>3</sup>/h]</b>	0.3 m <sup>3</sup> /h
<b>Maks. radni tlak [bar]</b>	70 bar
<b>Maks. radni tlak [psig]</b>	1015 psig
<b>MinODP [bar]</b>	0.02 bar
<b>MOP (maksimalni radni tlak) [bar/psi]</b>	Coil Dependent
<b>Napomena o rasponu temperature medija</b>	Defrost max. 130°C/265°F
<b>Oblik ambalaže</b>	Industrijsko pakiranje
<b>Odobrenje</b>	EAC LLC CDC TYSK UR
<b>Opcija ručnog rukovanja</b>	Ne
<b>Oznaka vrste</b>	Elektromagnetski ventil, lem
<b>Pribor proizvoda</b>	Pribor za elektromagnetski ventil
<b>Radne tvari</b>	R1233zd(E) R1234yf

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



## PRODUCT DETAILS

---

	R1234ze(E)
	R1270
	R134a
	R22/R407C
	R23
	R290
	R32
	R404A/R507A
	R407A
	R407F
	R407H
	R410A
	R422B
	R422D
	R438A
	R444B
	R448A
	R449A
	R449B
	R450A
	R452A
	R452B
	R454A
	R454B
	R454C
	R455A
	R463A
	R513A
	R513B
	R515A
	R515B
	R516A
	R600
	R600a
	R744

---

## Radne tvari koje je odobrio UL

R1233zd(E)
R134a
R22
R23
R290
R404A
R407A
R407C
R407F
R407H
R410A
R422B
R422D
R438A
R448A
R449A
R449B
R450A
R452A
R463A



## PRODUCT DETAILS

	R507A
	R513A
	R513B
	R515A
	R515B
	R516A
	R744
<b>Raspon temperature medija [°C] [Max.]</b>	105 °C
<b>Raspon temperature medija [°C] [Min.]</b>	-40 °C
<b>Raspon temperature medija [°F] [maks.]</b>	221 °F
<b>Raspon temperature medija [°F] [min.]</b>	-40 °F
<b>SCIP dossier no.</b>	ea5d532d-b171-4661-b0cd- f6cd93d69116
<b>SCIP dossier product name</b>	EVU 1-8
<b>Smjer</b>	Ravno
<b>Sustav pogona [mm]</b>	9 mm
<b>Svitak</b>	Ne
<b>Temperatura okoliša</b>	-40 - Coil dependent
<b>Tvari s popisa kandidata u skladu s Uredbom REACH</b>	Lead (CAS no. 7439-92-1)
<b>Veličina izlaza [mm]</b>	10 mm
<b>Veličina ulaza [mm]</b>	10 mm
<b>Vrsta izlaznog priključka</b>	Lemni priključak, ODF
<b>Vrsta ulaznog priključka</b>	Lemni priključak, ODF

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)