

Date 30/9/2025
 For the attention of:
 Reference
 Operator



COMMERCIAL UNIT COOLER:CUBIC

Type: F31HC 346 AC E 7

N. units: 1

Refriger (u) 2025 Ver. 2.4.3.410 - PRICE LIST 1/06/2025

Inlet air temp. (room)	[°C]	-20,0
Room relative humidity	[%]	85
Refrigerant		R449A
Altitude	[m]	0
Residual static pressure	[Pa]	0
DT1 needed for unit cooler (Dew)	[K]	7,0

Connection 230V-1PH-50Hz

Actual capacity	[W]	9.300
Air flow	[m3/h]	6.600,0
Air throw	[m]	25
Outlet air temperature	[°C]	-23,2
Evaporating temp (Dew)	[°C]	-27,0
DT superheating (Dew)	[K]	5,0
Temp. before expansion valve	[°C]	30,0
DT1 (Dew)	[K]	7,0
DTmlg	[K]	5,2
Fluid pressure drop	[K]	2,0
RC factor (Sensible capacity/Total capacity)	[%]	90,9
Energy efficiency class		C (2023 thresholds)
Fan motor consumpt.	[W]	408
Power draw	[A]	2,0
Max fan absorbed current*	[A]	2,08
Fan speed	[1/min]	1290
Sound pressure level (5 m) 5	[dB(A)@5m]	50
Sound Power Level	[dB(A)]	75
Electric defrost (230 V)	[W]	8.575
N° Fans	[mm]	4 x 315
Poles	[n]	4
Fin spacing	[mm]	7
Internal volume	[dm3]	8,1
Surface	[m2]	35,6
Max Working pressure	[bar]	24,0
Casing material	Powder coated galvanized steel RAL 9003	Fin material Al
Header material	Cu	Tube material Cu
Weight	[kg]	76
Connections in	[n] x [mm]	1 x 16
Connections out	[n] x [mm]	1 x 35
Drain tray connection	["]	3/4
Overall dimensions	[mm]	2.110 x 450 x 415

* Refer to LU-VE S.p.A. instruction manuals for details, data and standards. Noise level in 5m free field. The current may increase according to temperature frost quantity, external static pressure. The weight and dimensions are not valid for all possible configurations. All fans are ErP 2015-compliant (Directive 2009/125/EC Energy-related products). LU-VE S.p.A. reserves the right to modify and correct at any time, with or without notice, the specifications and prices listed in the Refriger software. For products manufactured in the Russian Federation please contact the sales office. Specification related to ventilator voltage (Volt), current (Ampere), electrical power (kW) are available [here](#). The specification is related to a single ventilator.

EUROVENT – CERTIFY ALL! Eurovent certification guarantees thermal performance, sound specifications, electrical power consumption, air volume flows. The certified performances and conditions in this software are in line with performances and conditions published on EUROVENT website.

LU-VE Group participates in the ECP programme for HE. Check ongoing validity of certificate and performance on www.eurovent-certification.com.

The EUROVENT certification refers to the unit in standard configuration, additional options may impact on declared reference performance.

Unit list value	1 x 3.616,00 €	Delivery
Total List Value	3.616,00 €	Payment conditions
Discount	%	Offer Validity
Accessories discount	%	
Total net Value	3.616,00 €	