

**111B5398****Pločasti izmjenjivač topline (eng. Micro Plate), MPHE C62L-EZ, Broj ploča: 80**

Maks. radni tlak [bar]: 45, Rashladnik, Funkcija: Isparivač, Legura za
lemljenje: Tvrdo lemljenje bakra

PRODUCT DETAILS

Bruto težina	15.15 Kilogram
Neto težina	15 Kilogram
Volumen	12.874 Cubic decimeter
Type	MPHE C62L-EZ
Product group	Izmjenjivači topline
Product Name Description	Pločasti izmjenjivač topline (eng. Micro Plate)
Application	Rashladnik
Br. modela	62
Broj ploča	80
China RoHS compliance	Yes
Contains batteries	No
EU RoHS compliance	Yes
EU RoHS exemption clause	No
Funkcija	Isparivač
In scope of WEEE	No
Kategorija	II
Količina po obliku pakiranja	1 pc
Legura za lemljenje	Tvrdo lemljenje bakra
Maks. radni tlak [bar]	45 bar
Maks. radni tlak [psi]	653 psi
Materijal ploče	AISI 316L
Napomena o funkciji	S distributerom
Oblik ambalaže	Pojedinačno pakiranje
Odobrenje	AS CRN EAC KRAIA PED RoHS UA UL
Oprema	Null
Oznaka vrste	C62L-EZ
Plate material no.	AISI 316L
Projektni raspon temperature [°C] [maks.]	200 °C
Projektni raspon temperature [°C] [min.]	-196 °C

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



PRODUCT DETAILS

Projektni raspon temperature [°F] [maks.]	320 °F
Projektni raspon temperature [°F] [min.]	-390 °F
Radne tvari	R1233zd(E) R1234yf R134a R22 R245fa R290 R404A R407C R410A R444B R448A R449A R450A R452B R454B R454C R455A R507A R513A R515B R1234ze R454A
Raspon vel. priklj. Q1	N1/2K
Raspon vel. priklj. Q2	N1/2K
Raspon vel. priklj. Q3	H5/8A
Raspon vel. priklj. Q4	H1"3/8H
Raspon vel. priklj. Q5	Null
Raspon vel. priklj. Q6	Null
Tvari s popisa kandidata u skladu s Uredbom REACH	No
UL evaluated	Yes
Uzorak ploče	Z
Vel. priklj. H1	G1"1/2
Vel. priklj. H2	G1"1/2
Vel. priklj. H3	Null
Vel. priklj. H4	Null
Vel. priklj. H5	Null
Vel. priklj. H6	Null
Vrsta priklj. H1	Vanjski navojni priključak G
Vrsta priklj. H2	Vanjski navojni priključak G
Vrsta priklj. H3	Null
Vrsta priklj. H4	Null
Vrsta priklj. H5	Null
Vrsta priklj. H6	Null
Vrsta priklj. Q1	Unutarnji navojni priključak G
Vrsta priklj. Q2	Unutarnji navojni priključak G
Vrsta priklj. Q3	Lemni priključak
Vrsta priklj. Q4	Lemni priključak
Vrsta priklj. Q5	Null

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**PRODUCT DETAILS**

Vrsta priklj. Q6Null

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)