

Refrigerant	R449A Dew Point
High Side Properties:	
Condensing Temperature, °C	42.50
Abs. Condensing Pressure, bar	17.73
Dew Point, °C	42.50
Bubble Point, °C	38.20
Saturated vapour enthalpy, kJ/kg	414.00
Specific volume of saturated vapour, dm ³ /kg	12.10
Low Side Properties:	
Evaporating Temperature, °C	-10.00
Evaporating Abs. Pressure, bar	3.61
Dew Point, °C	-10.00
Bubble Point, °C	-15.40
With vapour at, °C	20.00
Specific volume, dm ³ /kg	72.50
Enthalpy, kJ/kg	421.00
Operating Conditions:	
Evaporating Temperature, °C	-10.00
Suction Return Temperature, °C	20.00
Ambient, °C	32.00
Condensing Unit Selected	ZXDE-075E-TFD

**PERFORMANCE AT SPECIFIED OPERATING POINT
ZXDE-075E-TFD Data at 50 Hz**

Cooling Capacity, kW	11.40
Total Power Input, kW	4.83
COP	2.36
Current at 400 V, A	8.84
Mass Flow, g/s	69.90
Heating Capacity, kW	15.75
Condensing Temperature, °C	42.50
Subcooling at the Unit's outlet, K	0.00

CONDENSING UNIT MECHANICAL AND PHYSICAL DATA

Condenser/Fan Type	ZX075E/60 W
Number of Fans	2
Total Fan Power Input, W	246
Depth/Width, mm	1035/447
Height, mm	1244
Base mounting (hole dia), mm	580 x 388 (12)
Net Weight, kg	118
Receiver Capacity, l	5.9
Liquid Line, inch	1/2
Air Flow, m ³ /s	1.64
High Side PS gauge, bar	28.8
Low Side PS gauge, bar	21
Suction Type	Cu Tube
Suction Diameter, inch	7/8
Sound Pressure @ 10m (MT), dBA	42
Sound Conditions (MT, Temperatures: Evap./Cond./Suction at freq./speed)	-10.0/45.0/20.0 °C at 50 Hz

CONDENSING UNIT ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Compressor Maximum Operating Current, A	14
Compressor Locked Rotor Current, A	100

ACCESSORIES INCLUDED

Crankcase Heater	70 W External
Liquid Injection	DTC Valve
Oil separator	ALCO OSH-404
Liquid sight glass	ALCO MIA 012
Compressor contactor	12 A
Control circuit fuse	S7-904-5355-0
HP Switch	ALCO PS3 WDS (Automatic reset)
Electronic controller	Emerson XCM25D
Filter Drier	ALCO ADK Plus
Circuit breaker, over current relay	20 A

ACCESSORIES OPTIONAL

LP Adjustable Pressure Switch	Alco PS1-A3A
-------------------------------	--------------

