



embraco

LU-VE EXCHANGERS



Raspoloživi kapaciteti:

Kond. jedinica	Temp. u komori	Isparivač	Rashl. kapacitet (W)	
MT				
UNEK6210GK	230V/1PH	2°C	SHS12	653
UNEK6213GK	230V/1PH	2°C	SHS13	880
UNEK6217GK	230V/1PH	2°C	SHS18	1078
UNT 6222GK	230V/1PH	2°C	SHS22	1325
UNT 6226GK	230V/1PH	2°C	SHS26	1710
UNJ 9232GK	230V/1PH	2°C	SHS26	1901
UNJ 9238GK	230V/1PH	2°C	SHS32	2364
UNJX6250GS	230V/1PH	2°C	FHA41	3110
USE6015GS	380V/3PH	2°C	FHA53	3600
USE6018GS	380V/3PH	2°C	FHA53	4200
USE6021GS	380V/3PH	2°C	FHA79	4690
LT				
UNJ2192GJ	230V/1PH	-20°C	F27HC16	708
UNJ2212GK	230V/1PH	-20°C	F27HC16	883
UNJX2219GS	380V/3PH	-20°C	F27HC23	1150
USE2006GS	380V/3PH	-20°C	F27HC23	1200
USE2008GS	380V/3PH	-20°C	F27HC31	1510

Komplet rashladne opreme za rashladne komore

- ✓ Otvorena kondenzacijska jedinica Embraco Aspera
- ✓ Isparivač LU-VE s elektrogrijačima (razmak lamela 5 ili 7 mm)
- ✓ Termoekspanzijski ventil Danfoss
- ✓ Filter-sušač Danfoss
- ✓ Magnetski ventil Castel
- ✓ Kontrolno staklo Castel
- ✓ Presostati Ranco
- ✓ Mikroprocesorski kontroler Dixell ili Eliwell
- ✓ Temperaturne sonde (2 kom)

Danfoss

Castel
Italian technology

dixell®

*Napomena: Slike služe samo kao ilustracija.